

3M™ 5-Way Penetrant

3M Distributor
(+34) 912 30 24 69

Product Data Sheet

Date: January 2009
Supersedes: Date: November 2008

Product Description

Useful in a substantial quantity of applications, the 3M 5-Way Penetrant lubricates, demoiaturizes, cleans and helps prevent rust.

The 3M 5-Way Penetrant is available in an aerosol can and also as a pump spray version.

Key Features

- ▲ Lubricant
- ▲ Demoiaturant
- ▲ Silicone-Free

Typical Uncured Properties

	3M 5-Way Penetrant Pump Spray	3M 5-Way Penetrant Aerosol
Base	Mineral Oil	Mineral Oil
Colour	Transparent	straw
% Volatile	0	Isobutane 5 -25 Propane 5 -25
Density (g/cm³)	0.86	0.72
Odour	Petroleum	Solvent
Flash Point	>210 °C	- 46°C

Application Techniques

Usage of 3M 5-Way Penetrant Pump Spray:
Hold container upright and pump to dispense product. Fast pump action dispenses product as a spray, whilst a slower pump action gives a jet like spray.

For hard to reach areas, use the extension tube which fits into the spray head.
Thoroughly wet all grease, grime etc. On the surface or parts being cleaned with 3M 5-Way Plus Penetrant.
Wait for a few minutes for complete penetration and loosening action. Wipe thoroughly with a clean cloth.

Application Ideas

- ▲ Helps free rusted, frozen nuts and bolts
- ▲ Excellent light duty lubricant for many delicate or precision instruments
- ▲ Ideal tapping lubricant for stainless steel and aluminium
- ▲ Displaces moisture and "dries out" electrical apparatus, generators, motors
- ▲ Inhibits corrosion and printing of injection moulding dyes and extension screws during storage

Shelf Life	24 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity
Precautionary Information	Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information please contact your local 3M Office. www.3M.com
For Additional Information	To request additional product information or to arrange for sales assistance, call 0870 6080050 Address correspondence to: 3M United Kingdom PLC, 3M House, 28 Great Jackson Street, Manchester, M15 4PA
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.

3M United Kingdom PLC 3M House, 28 Great Jackson Street, Manchester, M15 4PA	Product Information : Tel 0870 60 800 50 Fax 0870 60 700 99	3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18, Ireland	Customer Service : Tel (01) 280 3555 Fax (01) 280 3509
--	---	--	--